

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

U.S. APPLICATION NO. (If known see 37 C.F.R. 1.5)

09/700150

INTERNATIONAL APPLICATION NO.
PCT/JP00/01472INTERNATIONAL FILING DATE
MARCH 10, 2000(EARLIEST) PRIORITY DATE CLAIMED
MARCH 11, 1999

TITLE OF INVENTION

INFORMATION RECEIVING DEVICE AND INFORMATION
RECEIVING METHOD

APPLICANT(S) FOR DO/EO/US

Fumio NAGUMO

Applicants herewith submit to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to promptly begin national examination procedures (35 U.S.C. 371(f)).
4. ☐ The US has been elected by the expiration of 19 months from the priority date (PCT Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is attached hereto (required only if not communicated by the International Bureau).
 - b. ☒ has been communicated by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
 - b. ☐ have been communicated by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
8. ☐ A English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).


Items 11 to 16 below concern document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A FIRST preliminary amendment.


EXPRESS MAILMailing Label Number: **EL585033310US**Date of Deposit: **November 9, 2000**

I hereby certify that this paper or fee is being deposited with the United States Postal Service

"Express Mail Post Office to Addressee" Service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents and Trademarks, Box PCT Washington, DC 20231.



(Typed or printed name of person mailing paper or fee)



(Signature of person mailing paper or fee)

PCT/RO/101, PCT/IB/301,304,308

PCT/ISA/220, 210

11 Sheets of Drawings, 1 Page Abstract

U.S. APPLICATION NO.(If known, see 37 C.F.R. 1.50)

INTERNATIONAL APPLICATION NO.

ATTORNEY'S DOCKET NO.

PCT/JP00/01472

450108-02376

17. ☒ The following fees are submitted

(CALCULATIONS /PTO USE ONLY)

Basic National Fee (37 CFR 1.492(a)(1)-(5):

Neither international preliminary examination fee (37 CFR 1.482)
nor international search fee (37CFR 1.445(a)(2)) paid to USPTO
and International Search Report not prepared by the EPO or JPO \$1,000.00

International preliminary examination fee (37 C.F.R. 1.482) not paid to
USPTO but International Search Report prepared by the EPO or JPO..... \$ 860.00

International preliminary examination fee (37 CFR 1.482) not paid to USPTO but
international search fee (37 CFR 1.445(a)(2)) paid to USPTO..... \$ 710.00

International preliminary examination fee paid to USPTO (37 CFR 1.482)
but all claims did not satisfy provisions of PCT Article 33(1)-(4). \$ 690.00

International preliminary examination fee paid to USPTO (37 CFR 1.482)
and all claims satisfied provisions of PCT Article 33(1)-(4) \$ 100.00

ENTER APPROPRIATE BASIC FEE AMOUNT = (\$ 860.00)

Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☐ 30 (\$
months from the earliest claimed priority date (37 CFR 1.492(e)).

16 Claims /Number Filed / Number Extra /Rate (\$

Total Claims / 16 - 20 = / 0 /X \$18.00 (\$

Independent Claims / 5 - 3 = / 2 /X \$80.00 (\$ 160.00

MULTIPLE DEPENDENT CLAIM(S) (if applicable) /+ \$270.00 (\$

TOTAL OF ABOVE CALCULATIONS = (\$1,020.00

☐ Applicant claims small entity status. See 37 C.F.R. 1.27. The fees indicated above
are reduced by 1/2. (\$

SUBTOTAL = (\$1,020.00

Processing fee of \$130.00 for furnishing the English translation later than ☐ 20 ☐ 30 (\$
months from the earliest claimed priority date (37 CFR 1.492(f)). +

TOTAL NATIONAL FEE = (\$1,020.00

Fee for recording the enclosed assignments (37 CFR 1.21(h)). The assignment must be (\$
accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property + (\$

TOTAL FEES ENCLOSED = (\$1,020.00

(Amount to be: \$
refunded:

(charged: \$

a. ☒ A check in the amount of \$1,020.00 to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees.
A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit
Account No. 50-0320. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the
application to pending status.

SEND ALL CORRESPONDENCE TO:

**WILLIAM S. FROMMER
FROMMER LAWRENCE & HAUG LLP
745 FIFTH AVENUE
NEW YORK, NEW YORK 10151**

SIGNATURE

William S. Frommer
NAME

Dated: November 9, 2000

25,506
REGISTRATION NUMBER

11/PRTS

DESCRIPTION

INFORMATION RECEIVING DEVICE AND INFORMATION RECEIVING METHOD

TECHNICAL FIELD

The present invention relates to an information receiving device for receiving information and an information receiving method and especially relates to the information receiving device and the information receiving method that make the viewer capable of setting the condition of information contents.

BACKGROUND ART

At present the television station places programs and CMs on the fixed places of the television program to be telecast and the viewer just receives and watches the broadcast program in which programs and CMs are placed at the time of broadcasting. As the broadcasting pattern in which CMs are placed on the program, there exist the pattern of placing programs and CMs alternately in time division and the pattern to broadcast CMs and programs simultaneously by placing CMs over the programs as Telop (television opaque), and the programs and CMs are placed on the same channel and are telecast.

However, according to these broadcasting patterns, it has created a problem that the viewer's desire to the CM broadcasting, such as the CM deletion request in exchange for the additional fee

payment, the CM acceptance request on condition that the fee for paid broadcasting would be reduced, and the category selection request of CMs being telecast, would not be reflected at all.

Furthermore, in such broadcasting patterns, since the across-the-board CM broadcasting has been conducted without considering age, sex, occupation and hobby of the viewer, the efficiency of CM has not been satisfactory.

DISCLOSURE OF THE INVENTION

The present invention has been done considering the above points and the object of the present invention is to provide an information receiving device and an information receiving method that make the viewer is capable of personally setting or not setting the display of CM and setting the category of CM to be displayed.

To obviate such problems according to the present invention, in the broadcasting system to which the viewers can set the condition of broadcast contents, we provide a broadcast receiving device comprising; the program receiving means for receiving program broadcasts, the CM receiving means for receiving the CM broadcasts, the broadcast contents recording means for recording broadcast contents, the condition setting means for conducting the display condition setting of CM broadcasts, the control means for controlling the broadcast contents to be displayed.

At this point, the broadcasting device broadcasts the

program broadcast and the CM broadcast. The broadcast receiving device stores the program broadcast and CM broadcast received, and displays programs and CMs according to the CM display condition selected by the viewer.

Furthermore, the broadcast receiving device that makes the viewer can set the condition of broadcast contents, we provide the broadcast receiving device comprising; the program receiving means for receiving program broadcasts, the CM receiving means for receiving CM broadcasts, the broadcast contents recording means for recording the broadcast contents, the condition setting means for setting the display condition of the CM broadcast, and the control means for controlling the broadcast contents to be displayed.

At this point, the program receiving means receives the main program broadcasting and the CM receiving means receives the CM broadcasting, the broadcast contents recording means records contents of broadcasts, the condition setting means sets the display condition of CM broadcasting to be selected by the viewer, and the control means controls contents of broadcasting to be displayed.

Furthermore, in the broadcast receiving method that makes the viewer can set the condition of broadcasting contents, we provide the broadcast receiving method for receiving the program broadcast, receiving the CM broadcast, recording contents of broadcast received, display setting the CM broadcast to be

displayed, and for controlling contents of broadcasting to be displayed.

According to this method, the program broadcasts and CM broadcasts received are recorded and the CM broadcast will be displayed according to the condition set by the viewer.

BRIEF DESCRIPTION OF DRAWINGS

Fig. 1 is a systematic diagram according to the first embodiment.

Fig. 2 is a schematic diagram showing the state in which the program data of Ch.A and the CM data of Ch.B are combined.

Fig. 3 is a systematic diagram according to the second embodiment.

Fig. 4 is a schematic diagram showing the state in which the program data of Ch.A and the CM data of Ch.B are combined.

Fig. 5 is a systematic diagram according to the third embodiment.

Fig. 6 is a schematic diagram showing the state in which the program data of Ch.A and the CM data are combined.

Fig. 7 is a schematic diagram showing the program broadcasting information.

Fig. 8 is a schematic diagram showing the CM data.

Fig. 9 is a brief linear statistic diagram showing the condition setting means 25 of Fig. 5 in detail.

Fig. 10 is a schematic diagram showing the program data.

Fig. 11 is a schematic diagram showing the classification CM combined data.

Fig. 12 is a schematic diagram showing the classified CM combined data.

Fig. 13 is a brief linear diagram showing the CM combined data at the time when the number of CM displays is specified.

Fig. 14 is a systematic diagram showing the program providing means according to the other embodiment.

BEST MODE FOR CARRYING OUT THE INVENTION

The present invention will be described in detail with reference to the accompanying drawings.

Firstly, the first embodiment will be described hereunder.

Fig. 1 is a brief linear diagram according to the first embodiment. The broadcasting system 1 of the present embodiment comprises a broadcasting device 10 for conducting the program and CM broadcasting and a broadcast receiving device 20 owned by the viewer for receiving the broadcast.

The broadcasting device 10 comprises the program transmission means 11 for transmitting program broadcasts and the CM broadcasting means 12 for transmitting CM broadcasts. The broadcast receiving device 20 comprises the program receiving means, Ch.A tuner 21, the CM receiving means, Ch.B tuner 22, the broadcast contents recording means 23 for recording the CM broadcast received at the Ch.B tuner 22 as CM data, the control

means 24 for controlling the broadcast contents to be displayed and transmitting the display result to the commercial broadcasting company, the condition setting means 25 for entering the display condition of CM broadcasts, and a combiner 26 for combining the program data received by the Ch.A tuner 21 and the CM data extracted from the broadcast contents recording means 23.

The broadcast contents recording means 23 is electrically connected to the Ch.B tuner 22, the combiner 26 and the control means 24. And the control means 24 is connected electrically to the condition setting means 25. And the Ch.A tuner 21 is electrically connected with the combiner 26.

Then, the function of the broadcasting system 1 according to the present embodiment will be described in the following paragraphs.

Firstly, the viewer who uses the broadcasting system 1 conducts the display condition setting of CM by using the condition setting means 25 of the broadcast receiving device 20 which the viewer owns by himself. As the display condition to be set, such as CM will be displayed or not, the classification of CM to be displayed, the viewer's sex, age, occupation and hobby can be listed.

The display condition entered by the condition setting means 25 is transmitted to the control means 24 and recorded on the recording device such as RAM (random access memory) in the control means 24. On the other hand, the broadcasting device 10 transmits

the program broadcast concerning the program contents by the program transmission means 11 and transmits the CM broadcast related to the CM contents by the CM transmission means 12. At this point, the program broadcast and CM broadcast are transmitted via different channels respectively, and in this case, the program broadcast is transmitted via the Ch.A tuner and the CM broadcast is transmitted via the Ch.B tuner.

The program broadcasts and the CM broadcasts transmitted will be received by the broadcast receiving device 20 owned by the viewer per channel. In this case, the program broadcasts are received by the Ch.A tuner 21, and the CM broadcasts are received by the Ch.B tuner. Then, the program broadcasts and CM broadcasts received are captured into the broadcast receiving device 20 as the program data and CM data respectively. The program data captured is reached to the combiner 26, while the CM data is recorded on the broadcast contents recording means 23.

The CM data recorded on the broadcast contents recording means 23 is invoked according to the setting condition recorded on the recording device in the control means 24, and the CM data invoked will reach to the combiner 26. Then the CM data reached to the combiner 26 is combined with the program data and transmitted to the display.

Fig. 2 is a diagram showing the state in which the program data 31 of Ch.A and the CM data 32 of Ch.B are being combined. In this figure the horizontal axis shows the time axis.

The program transmission means 11 of the broadcasting device 10 broadcasts program contents for the fixed period of time continuously by the Ch.A. And then, it stops the broadcasting of program contents for the fixed period of time and then starts the broadcasting of program contents continuously for the fixed period of time. Thus, the program transmission means 11 repeats these processings. Accordingly, the program data 31 to be received by the Ch.A consists of programs of A1, A2 and A3, that will be broadcasted continuously for the fixed period of time and the inactive period 31a during which no program to connect each program is broadcasted.

Furthermore, the CM transmission means 12 of the broadcasting system 10 broadcasts CM contents for the fixed period of time continuously by the Ch.B. Thus, the CM data 32 to be received by the Ch.A consists of only CMs, such as a, b, c.

The CM data 32 recorded on the broadcast contents recording means 23 will be selected according to the setting condition recorded on the recording device in the control means 24. In the case of Fig. 2, CMs of a, c and f are selected from the CM data 32 in accordance with the setting condition. Thus selected CM is invoked so that the inactive period 31a of the program data and its timing agree and transmitted to the combiner 26.

The combiner 26, by combining the program data 31 transmitted from the Ch.A and the CM invoked from the broadcast contents recording means 23 as described above, forms CM combined

data 33. The CM combined data 33 is comprised of programs of A1, A2 and A3 placed at the same timing as the programs forming the program data 31 and the CMs of a, c and f placed at the same timing as the inactive period 31a of the program data 31.

Thus formed CM combined data 33 is transmitted to the display and the display is conducted using this CM combined data 33.

Thus, when the display is actually conducted, the control means 24 transmits the customer requirements such as customer information and the display condition and the information on the number of CM displays to the commercial broadcasting company. The commercial broadcasting company upon receiving the customer requirement such as customer information, display condition and the information on the number of CM displays, sets the program viewing fee for each viewer based on said information.

According to the present embodiment as described above, since the program broadcast and the CM broadcast are transmitted by the broadcasting device 10 via different channels, and the broadcast receiving device 20 receives the program broadcast and the CM broadcast transmitted via different channels as the program data 31 and the CM data 32, and records the CM data 32 once on the broadcast contents recording means 23, and the control means 24 invokes CM from the CM data 32 recorded according to the condition set by the condition setting means 25 in advance and placing this on the inactive period 31a of the program data 31, forms the CM

combined data 33 and displays this CM combined data 33 on the display, the viewer becomes possible to view only CMs that reflect the viewer's personal desire.

Furthermore, according to the present embodiment, since only the CMs to which the viewer personally sets the condition can be displayed on the viewer's display, the CM advertising efficiency can be remarkably improved.

In this connection, according to the present embodiment, CMs are placed on the inactive period 31a of the program data. However, the CMs may be placed over the programs of the program data 31 as Telop.

Next, the second embodiment will be described in the following paragraphs.

Fig. 3 is a systematic diagram showing the second embodiment.

The broadcasting system 1 of this embodiment comprises a broadcasting device 10 for broadcasting programs and CMs and a broadcast receiving device 20 owned by the viewer for receiving the broadcast.

The broadcasting device 10 comprises the program transmission means 11 for transmitting program broadcasts and the CM broadcast means 12 for transmitting CM broadcasts. The broadcast receiving means 20 comprises a Ch.A tuner 21 which is the program receiving means and for receiving program broadcasts, a Ch.A tuner 22, which is the CM receiving means for receiving the CM broadcast, the broadcast contents recording means 23 for

recording the program broadcast received by the Ch.A tuner 21 as the program data and the CM broadcast received by the Ch.B tuner 22 as the CM data, the transmission control means 24 for controlling the broadcast contents to be displayed and for transmitting the display results to the commercial broadcasting company, and the condition setting means 25 for entering the display condition of the CM broadcasts.

The broadcast contents recording means 23 is electrically connected to the Ch.A tuner 21, Ch.B tuner 22 and the control means 24, and the control means 24 is connected electrically to the condition setting means 25.

Next, the function of the broadcasting system 1 according to the present embodiment will be described as follows.

Firstly, the viewer who uses the broadcasting system 1 conducts the CM display condition setting by means of condition setting means 25 of the broadcast receiving device 20 owned by each viewer. The display condition entered by the condition setting means 25 is transmitted to the control means 24 and recorded on the recording device in the control means 24.

On the other hand, the broadcasting device 10 transmits the program broadcast by the program transmission means 11 and transmits the CM broadcast by the CM transmission means 12. At this point, the program broadcast and the CM broadcast are transmitted via separate channels respectively. In the case of Fig. 3, the program broadcast is transmitted via the Ch.A and the CM

broadcast is transmitted via the Ch.B.

The program broadcast and the CM broadcast transmitted are received by the broadcast receiving device 20 per channel. In this case, the program broadcast is received by the Ch.A tuner 21, and the CM broadcast is received by the Ch.B tuner. Then, the program broadcast and the CM broadcast received are recorded on the broadcast contents recording means 23 as the program data and the CM data respectively.

The program data and the CM data recorded on the broadcast contents recording means 23 are combined in accordance with the setting condition recorded on the recording device in the control means 24 and transmitted to the display.

Fig. 4 is a diagram showing the state in which the Ch.A program data 31 and the Ch.B CM data 32 are being combined. The horizontal axis of this figure shows the time axis.

The program transmission means 11 of the broadcasting device 10 broadcasts the program contents for the fixed period of time continuously by the Ch.A. Accordingly, the program data 31 to be received by the Ch.A is comprised of only A1, A2, A3 programs.

Moreover, the CM transmission means 12 of the broadcasting device 10 broadcasts the CM contents for the fixed period of time continuously by the Ch.B. Accordingly, the CM data 32 to be received consists of only CM programs such as a, b, c.

The control means 24 reads out the CM selected from the CM data 32 from the broadcast contents recording means 23 according

to the condition set by all program data 31 and the condition setting means 25 and forms the CM combined data 33 by placing CMs before and after programs. In the case of Fig. 4, CMs of a, c, f are selected, and the CM of a is placed before the program A1, the CM of c is placed between the programs A1 and A2, and the CM of f is placed between the program A2 and the program A3. In this case, since CMs are inserted between the program data being transmitted continuously, the CM combined data 33 will delay by CMs inserted. In this connection, if the viewer refuses the CM display, CM would not be inserted and the CM combined data 33 would not delay with respect to the program data 31.

Thus formed CM combined data 33 is transmitted to the display and the display is conducted by this CM combined data 33.

Thus, when the display is actually conducted, the control unit 24 transmits the customer requirement such as customer information, display condition and the information such as the number of CM displays to the commercial broadcasting company. The commercial broadcasting company, upon receiving the customer requirement such as display condition and the information such as the number of CM displays, sets the program viewer's fee of each viewer based on said information.

According to the embodiment of the present invention as described above, the broadcasting device 10 transmits the program broadcast and the CM broadcast via different channels, the broadcast receiving device 20 receives the program broadcast and

the CM broadcast transmitted via separate channels as the program data 31 and the CM data 32 and records these program data 31 and CM data 32 received on the broadcast contents recording means 23 once, and the control means 24 reads out the program data 31 and CM selected from the CM data 32 from the broadcast contents recording means 23 and placing these alternately, forms the CM combined data 33 and the CM combined data will be displayed. Thereby, the viewer becomes possible to view only CMs that reflect the viewer's personal desire.

Furthermore, according to the present embodiment, since only CMs to which the viewer personally sets the condition are to be displayed on the viewer's display, the efficiency of CM advertising can be remarkably increased.

Furthermore, the embodiment described above has dealt with the case of placing CMs between programs of the program data 31. However, CMs may be placed over the programs of the program data 31 as Telop.

Then, the third embodiment will be described in the following paragraphs.

Fig. 5 is a systematic diagram according to the third embodiment.

The broadcasting system 1 of this embodiment comprises the broadcasting device 10 for broadcasting the programs and CMs and the broadcast receiving device 20 owned by the viewer who receives the broadcasts.

The broadcasting device 10 comprises the program transmission means 11 for transmitting program broadcasts and the CM transmission means 1 for transmitting CM broadcasts. The broadcast receiving means 12 is comprised of the Ch.A tuner 21 which is the program receiving means and CM receiving means for receiving the program broadcasts and the CM broadcasts, the broadcast contents recording means 23 for recording the program broadcasts and CM broadcasts received at the Ch.A tuner 21 as the program data and the CM data the transmission control means 24 for controlling the broadcast contents to be displayed and for transmitting the display results to the commercial broadcasting company, and the condition setting means 25 for entering the display condition of CM broadcasts.

The broadcast contents recording means 23 is electrically connected to the Ch.A tuner 21 and the control means 24, and the control means 24 is connected electrically to the condition setting means 25.

Then, the function of the broadcasting system 1 according to the present embodiment will be explained.

Firstly, the viewer who uses the broadcasting system 1 conducts the display condition setting of CM of the broadcast receiving device 20 which he owns.

The broadcasting device 10 transmits the program broadcast by the program transmission means 11 and transmits the CM broadcast by the CM transmission means 12. At this point, the

program broadcast and the CM broadcast are sent via the same channel shifting the transmission time alternately, such as the program broadcast is transmitted during the day time and the CM broadcast is transmitted during the mid-night.

The program broadcast and the CM broadcast transmitted are received by the Ch.A of the broadcast receiving device 20. Then the program broadcast and CM broadcast received are recorded on the broadcast contents recording means 23 as the program data and the CM data respectively.

The program data and the CM data recorded on the broadcast contents recording means 23 are combined according to the setting condition recorded on the recording device in the control means 24 and transmitted to the display.

Fig. 6 is a diagram showing the state in which the Ch.A program data 31 and the CM data 32 are combined. A horizontal axis of this figure shows the time axis.

The CM transmission means 12 and the program transmission means 11 of the broadcasting device 10 transmit the CM broadcast and the program broadcast via the same channel shifting the time period.

The CM transmission means 12 of the broadcasting device 10 broadcasts CM contents continuously for the fixed time period. Accordingly, the CM data 32 to be received by the Ch.A consists of only CMs such as a, b and c.

Furthermore, the program transmission means 11 of the

broadcasting device 10 broadcasts program contents continuously for the fixed time period. Therefore, the program data 31 to be received by the Ch.A consists of only programs of A1, A2 and A3.

The control means 24 reads out CMs selected from the CM data 32 according to the condition set by all program data 31 and condition setting means 25 from the broadcast contents recording means 23, and placing CMs before and after the programs, forms the CM combined data 33.

Thus formed CM combined data 33 will be transmitted to the display, and the display will be conducted by using this CM combined data 33.

Thus, when the display is actually conducted, the control means 24 transmits the customer requirement such as customer information, display condition and the information such as the number of CM displays to the commercial broadcasting company. The commercial broadcasting company, upon receiving the customer requirement such as customer information, display condition and the number of CM displays, sets the program viewing fee of each viewer based on said information.

According to the present invention as described above, the broadcasting device 10 transmits the program broadcasts and the CM broadcasts via the same channel shifting the time slot. The broadcast receiving device 20 receives the program broadcast and the CM broadcast transmitted as the program data 31 and the CM data 32 respectively, and records these program data 31 and CM

data 32 received on the broadcast contents recording means 23 once. The control means 24 reads out the program data 31 and the CM selected from the CM data 32 according to the condition set from the broadcast contents recording means 23 and forms the CM combined data 33 placing these alternately and the CM combined data 33 will be displayed on the display. Accordingly, the viewer becomes possible to view only CMs that reflect the viewer's personal desire.

Furthermore, according to the present embodiment, since the CM to which the viewer personally set the condition can be displayed on the display focussing only on this CM, the efficiency of CM advertising can be remarkably increased.

In this connection, according to this embodiment, CMs are placed between programs of the program data 31. However, CMs may be placed over programs of the program data 31 as Telop.

In the program data 31 comprising the program broadcasts, if blocks shown as A1, A2 and A3 are to be defined as the program block respectively, the address data to specify these program blocks are inserted to the predetermined positions of the program, i.e., head of each program block, as AD1, AD2 and AD3 respectively as shown in Fig. 7.

Furthermore, similarly in the CM data 32, if blocks shown by a, b, c, d, e, f, ... are defined as the CM block respectively, the ADCM address data to specify the CM blocks, ADCM1, ADCM2, ... ADCM5, ADCM6, are inserted to the predetermined position of the

block such as the head of each block as shown in Fig. 8.

Furthermore, as shown in Fig. 8, in each CM block a, b, c, d, e, f, data showing the classification of these CM blocks are inserted as CL1, CL2, CL3 following the CM address data. Accordingly, here CM blocks a and d, CM blocks b and e, and CM blocks c and f are regarded as CM data that belong to the same category.

More specifically, as shown in Fig. 8, CM blocks a and d can be considered as the CM data associated with cosmetics, CM blocks b and e can be considered as the CM data related to automobiles, and CM blocks c and f can be regarded as the CM data associated with housewares.

As a matter of course, CM blocks a and d may be the CM of the same cosmetics or these may be the CM of different cosmetics of the same company or these may be the cosmetics of different companies. And the same applies to CM blocks b. That is, these CMs may be of the same type of automobiles, or the CMs may be different types of automobiles, or the CMs of the different companies may do.

According to the third embodiment described in Fig. 5 will be explained in detail referring to Figs. 8 and 9 as follows. A more detailed example of the condition setting means 25 in Fig. 5 will be shown in Fig. 9.

Fig. 9 generally shows the condition setting means 25, and this condition setting means 25 comprises an information terminal

device 251 and a mouse 252 as the input means for inputting its condition. Of course, it is not necessary that the display screen would be included in the information terminal device 251 but the display that is not displayed on Fig. 5 may be used.

As shown in Fig. 9, a CM condition window 253 and a CM classification specifying window 254 are displayed on the display screen of the information terminal device 251. And the viewer desired CM condition and CM classification will be specified by a cursor 255 on the display screen using the mouse 252.

For example, when the viewer requests additional CMs hoping that the fee for the CM broadcast would be reduced, he may click the mouse by selecting the item "add" of the CM condition window 253 by moving the cursor 255.

If the viewer wants to enjoy the program from which the CM is deleted even though he has to pay an excess fee more or less, he may click the mouse selecting the item "delete" of the CM condition window 253.

Furthermore, if the viewer requests the specific CM only, he may click the mouse by selecting the item "classification request" of the CM condition window 253 as well.

Furthermore, if the viewer conducts the CM classification request using the CM condition window 253, he can select the desired CM classification from the classification displayed on the CM classification window 254 of the display device. In this case, the viewer, moving the cursor 255 in the CM classification window

by using the mouse 252, selects the desired CM classification and clicks.

With this arrangement, the condition setting data set by the viewer as described above will be transmitted to the control means 24 from the information terminal 251 (the condition setting means 25). The control means 24, transmitting the condition setting data obtained from the condition setting means to the commercial broadcasting company, transmits the control data to the broadcast contents recording means 23.

At the broadcast contents recording means 23, the program data and the CM data recorded will be combined in the predetermined order by the control data from the control means 24 and transmitted to the display as the CM combined data.

In the case where the viewer selects "add" on the CM condition window 253, all CMs (a, b, c, d, e, f) transmitted from the transmission means and recorded on the broadcast contents recording means 23 are inserted between program blocks in order regardless of the contents and classification of CM as shown in Fig. 6 and these are displayed on the display screen as the CM combined data 33.

Moreover, if the viewer selects "delete" on the condition window 253, as shown in Fig. 10 only the program data 31 is transmitted to the display from the broadcast contents recording means 23 and will be displayed.

Furthermore, if the viewer selects "cosmetic" on the CM

classification window 254 after selecting "classification request" on the condition window 253, for example, the broadcast contents recording means 23 extracts only the CM data related to cosmetics from the CM data shown in Fig. 8 based on the control data from the control means 24, and inserting these between program blocks A1, A2,... of the program data 31 respectively as shown in Fig. 11, forms the classification CM combined data. And this classification CM combined data formed will be displayed on the display screen.

Moreover, as shown in Fig. 12, if the viewer selects "automobile" on the CM classification window 254, the broadcast contents recording means 23 forms classification CM combined data in which only the CM data related to automobile are inserted between each program block A1, A2,... in the same manner as in the case described above. This classification CM combined data formed will be displayed on the display screen.

In this connection, only 3 types of CM conditions are displayed on the CM condition window 253 in Fig. 9. This is because to simplify the explanation and it is easily understandable that in practice, various other conditions can be set. And as described above, the number of CMs to be displayed is one of conditions.

In the case of specifying the number of CM displays, the specification, such as 90%, 80% ... 30%, 20%, 10% can be conducted. For example, if the specification of "90%" is conducted, nine (9) CM data will be combined to ten (10) program data blocks. And the

CM combined data in which according to the "80%" specification, 8 CM data are combined to 10 program data blocks, 7 CM data are combined to 10 program data blocks according to the 70% specification, 3 CM data are combined to 10 program data blocks according to the "30%" specification and 2 CM data are combined according to the "20%" specification, can be formed.

Fig. 13 shows examples of the 90% specification and 30% specification. In the case of 90% specification, CM1 is followed by the program block A1, CM2, A2, CM3, A3, ... CM9, A9, and up to this point CM blocks and program blocks are placed alternately, and the program block 10 is placed right after the program block A9. That is 9 CM blocks are placed with respect to 10 program blocks.

Similarly, in the case of 30% specification, CM1 is followed by A1, CM2, A2, CM3, A3, and after A3 only program blocks A4, A5, A6, ... A9, A10 are placed. More specifically, 3 CM blocks are placed with respect to 10 program blocks.

These data concerning the number of CM displays will be also transmitted to the commercial broadcasting company. The commercial broadcasting company sets the fee based on the data related to the number of CM displays.

As shown in Fig. 7, program blocks are added by addresses showing each block. More specifically, AD1, AD2, AD3 are added to program blocks A1, A2 and A3 respectively.

Furthermore, as shown in Fig. 8, CM blocks are also added by

addresses showing each block. Moreover, CM blocks are added by data showing the CM classification following addresses. In Fig. 8, as the data showing CM classifications, "CL1" is made as the classification data showing cosmetic, "CL2" is the classification data showing automobile, and "CL3" is the classification data to show housewares.

Based on the control data from the control means 24, the broadcast contents recording means 23 combines the program blocks and the CM blocks according to addresses. For example, if the CM condition "add" is selected by the condition setting means 25, control data are supplied to the broadcast contents recording means 23 by the control means. Then, the broadcast contents recording means 23 combines the program block (A1) having the address AD1 of the program block shown in Fig. 8 and the CM block (a) having the address ADCM1 of the CM block shown in Fig. 8.

Similarly, the program block (A2) will be combined with the CM block (b) based on the address AD2 and ADCM2, and the program block (A3) will be sequentially combined with the CM block of ADCM3. With this arrangement, the broadcast contents recording means 23 forms CM combined data in which program blocks and CM blocks are combined as shown in Fig. 8 and supplies to the display device 26.

Moreover, at the time when the CM classification request is conducted by the condition setting means 26, if the viewer desires only the cosmetic CM, the broadcast contents recording means 23

selects only CM blocks having the classification data "CL1" showing the CM of cosmetics from among CM blocks recorded and combines these with the program blocks. For example, the broadcast contents recording means 23 combines the program block A1 to which the address AD1 is attached shown in Fig. 7 and the CM block a having the classification data "CL1" and the address ADCM1 shown in Fig. 8. Then, similarly, it combines the program block A2 and the CM block d having the classification data "CL1" and the address ADCM4. With this arrangement, the broadcast contents recording means 23 forms the classification CM combined data shown in Fig. 11 or Fig. 12 and supplies these to the display device 26.

Furthermore, the following modification can be considered. The configuration of Fig. 14 in accordance with the present invention is constituted by the configuration shown in Fig. 5 to which the CM related information memory 28 is added. And changing the broadcasting device 10 to the program providing means 10, and the broadcast receiving device 20 to the program receiving means 20, the program providing means 10 and the program receiving means 20 are connected via a bidirectional bus or a net 27. According to the configuration as described above, the control data from the control means 24 will be transmitted to the program providing means 10 via said bidirectional bus or the net 27.

In the CM related information memory 28 various information relating to the CM data transmitted from the CM transmission means 12 are stored. Normally this CM related information would not be

transmitted to the program receiving device side, however, only when the viewer requests, this CM related information will be sent to the program receiving means via the bus or the net 27 and recorded on the broadcast contents recording means 23.

If the viewer wants to get more detailed information while he is watching CM, and he conducts the CM related information request by means of the condition setting means 25, his request is supplied as a request information to the bus or net 27 via the control means. Upon receiving this request information, the program providing means 10 extracts the predetermined CM related information from the CM related information memory 28 and these are recorded on the broadcast contents recording means of the program receiving means 20 via the CM transmission means 12, the bus or net 27.

According to the foregoing construction, when the viewer conducts the CM classification request and watches his desired CM only, he can further confirm the CM related information. More specifically, for example, when the viewer saw the CM of automobile, he can find information described on the catalog prepared at the car dealer, such as the capacity of the car, the number of models or a variety of optional devices, the price, the method of payment, etc.

According to the present invention as described above, since the program broadcast and CM broadcast transmitted from the broadcasting device are received respectively, these broadcasts

received are recorded on the broadcast contents recording means, and the control means forms the CM combined data to be displayed based on the condition set, the viewer becomes possible to watch only CMs that reflect the viewer's personal desire.

Furthermore, according to the present invention, since the CM to which the viewer personally sets condition is to be displayed on the viewer's display, the efficiency of CM advertising can be remarkably increased.

INDUSTRIAL APPLICABILITY

The present invention can be applied to the broadcasting system for broadcasting the broadcast information including commercial information.

CLAIMS

1. An information receiving device that makes the viewer can set the condition of information to be received, wherein:

said information comprising program information and commercial information, and comprising:

recording means for recording said information;

condition setting means for conducting the condition setting related to said commercial information recorded;

control data forming means for forming the control data showing the condition set by said condition setting means and for supplying to said recording means;

data transmission means for forming data showing the condition set by said condition setting means and for transmitting to the supplying source who supplies said information; and characterized by:

said recording means sets the combination of said program information and commercial information according to said control data.

2. An information receiving device as defined in Claim 1, wherein:

said condition setting means is capable of changing the combination ratio of said program information and commercial information.

3. An information receiving device as defined in Claim 2, wherein:

said condition setting means is capable of setting the deletion of said commercial information.

4. An information receiving device as defined in Claim 2, wherein:

said condition setting means is capable of selecting and setting the classification of said commercial information.

5. An information receiving device that makes the viewer can conduct the condition setting of information receivable, wherein:

said information consisting of program information and commercial information; and comprising:

recording means for recording said information;

condition setting means for conducting the condition setting on the commercial information recorded and for selecting commercial information;

control data forming means for forming control data showing the condition set by said condition setting means and for supplying this to said recording means;

data transmission means for forming data showing the condition set by the condition setting means and for transmitting this to the supplier who supplies said information; and characterized by:

said recording means sets the combination of said program information and the selected commercial information by said control data, and records the information related to the commercial information selected from said information supplier according to the data to be transmitted to said information supplier.

6. An information receiving method that makes the viewer can conduct the condition setting of information to be received, wherein:

aaid information consisting of program information and commercial information, and comprising:

a step for recording said information;

a condition setting step for setting the condition related to the commercial information recorded;

a control data forming step for forming the control data showing the condition set by said condition setting step and for supplying this to said recording means; and

a data transmission step for forming data showing the condition set by said condition setting step and for transmitting to the supplier who supplies said information; and characterized by:

said recording step sets the combination of said program information and commercial information by said control data.

7. An information receiving method as defined in Claim 1,
wherein:

said condition setting step changes the ratio of combination
of said program information and commercial information.

8. An information receiving method as defined in Claim 6,
wherein:

said condition setting step makes the deletion setting of
said commercial information possible.

9. An information receiving method as defined in Claim 7,
wherein:

said condition setting step makes the selection setting of
classification of said commercial information possible.

10. An information receiving device connected to the information
supplier via a bidirectional circuit, and as well as receiving the
program information and commercial information from said
information supplier, for transmitting the condition setting
request related to the commercial information to said information
supplier through said bidirectional circuit, comprising:

recording means for recording said program information and
said commercial information;

combining means for combining said program information and
commercial information;

condition setting means for setting the combination condition of said commercial information with respect to said program information on the screen;

condition data forming means for forming the condition data showing the condition set by said condition setting means and supplying to said bidirectional circuit, transmitting to said information supplying source; and

additional information request generation means for requesting additional information related to said commercial information to said information supplying source via said bidirectional circuit; and characterized by:

said combining means changes the combination ratio of the program information and the commercial information and records additional information related to said commercial obtained from said supplier based on said additional information request on said recording means.

11. A broadcast receiving device that makes the viewer can set the condition on the broadcast contents, comprising:

program receiving means for receiving program broadcasts;

CM receiving means for receiving CM broadcasts;

broadcast contents recording means for recording the broadcast contents;

condition setting means for conducting the display condition setting of the CM broadcasting; and

a control means for controlling the broadcast contents to be displayed.

12. A broadcast receiving device as defined in Claim 11,
wherein:

said condition setting means is capable of setting or non-setting of CM broadcast display.

13. A broadcast receiving device as defined in Claim 11,
wherein:

said condition setting means can select the CM broadcast contents to be displayed.

14. A broadcast receiving device as defined in Claim 11,
wherein:

said control means places CM broadcasts between program broadcasts according to the setting of said condition setting means.

15. A broadcast receiving device as defined in Claim 11,
wherein:

said control means places CM broadcasts between program broadcasts according to the setting of said condition setting means.

16. A broadcast receiving device as defined in Claim 11,
wherein:

said control mean informs the execution of CM broadcast
display to the outside.

ABSTRACT

The object of the present invention is to provide a broadcasting system, a broadcast receiving device and broadcast receiving method that make the viewer individually can conduct the setting or non-setting of CM display and the CM category to be displayed. The broadcasting device 10 transmits the program broadcast and the CM broadcast via separate channels; the broadcast receiving device 20 receives the program broadcast and the CM broadcast transmitted via separate channels as the program data and the CM data respectively and records the CM data once in the broadcast contents recording means 23, and the control means 24 invokes CM from the CM data recorded according to the condition set by the condition setting means 25 in advance, forms CM combined data by placing the CM invoked in the program data and displays on the screen using the CM combined data.




FIG. 1




FIG. 2




FIG. 3

FIG. 4 is a block diagram of a system for processing data from a sensor array.




FIG. 4




FIG. 5




FIG. 6




FIG. 7

CM DATA 32




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

REFERENCE NUMERALS

1...Broadcasting system, 10...Broadcasting device,
11...Program transmission means, 12...CM Transmission means,
20...Broadcast receiving device, 21...Ch.A tuner. 22...Ch.B tuner,
23...Broadcast contents recording means, 24...Control means,
25...Condition setting means, 27...Bidirectional bus or net,
28...CM related information memory

Declaration and Power of Attorney for Patent Application**特許出願宣言書及び委任状****Japanese Language Declaration****日本語宣言書**

私は、以下に記名された発明者として、ここに下記の通り宣言する：

As a below named inventor, I hereby declare that:

私の住所、郵便の宛先そして国籍は、私の氏名の後に記載された通りである。

My residence, post office address and citizenship are as stated next to my name:

下記の名称の発明について、特許請求範囲に記載され、且つ特許が求められている発明主題に関して、私は、最初、最先且つ唯一の発明者である（唯一の氏名が記載されている場合）か、或いは最初、最先且つ共同発明者である（複数の氏名が記載されている場合）と信じている。

I believe I am the original, first and sole inventor if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled.

**INFORMATION RECEIVING DEVICE AND
INFORMATION RECEIVING METHOD**

the specification of which is attached hereto unless the following box is checked:

上記発明の明細書はここに添付されているが、下記の欄がチェックされている場合は、この限りでない：

☒ was filed on March 10, 2000
as United States Application Number of
PCT International Application Number PCT/JP00/01472
_____ and was amended on
_____ (if applicable).

☐ _____ の日に出版され、
この出版の米国出版番号またはPCT国際出版番号は、
_____ であり、且つ
_____ の日に補正された出版（該当する場合）

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、上記の補正書によって補正された、特許請求範囲を含む上記明細書を検討し、且つ内容を理解していることをここに表明する。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

私は、連邦規則法典第37編規則1.56に定義されている、特許性について重要な情報を開示する義務があることを認める。

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the need of the individual case. Any comments on the amount of time you are required to complete this form should be sent to Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner of Patents and Trademarks, Washington, DC 20231.

日本語宣言書

私は、ここに、以下に記載した外国での特許出願または発明者証の出願、或いは米国以外の少なくとも一國を指定している米国法典第35編第365条(a)によるPCT国際出願について、同第119条(a)-(d)項又は第365条(b)項に基づいて優先権を主張するとともに、優先権を主張する本出願の出願日より前の出願日を有する外国での特許出願または発明者証の出願、或いはPCT国際出願については、いかなる出願も、下記の枠内をチェックすることにより示した。

Prior Foreign Application(s)

外国での先行出願

11-064416
(Number)
(番号)

Japan
(Country)
(国名)

PCT/JP00/01472
(Number)
(番号)

PCT
(Country)
(国名)

(Number)
(番号)

(Country)
(国名)

(Number)
(番号)

(Country)
(国名)

(Number)
(番号)

(Country)
(国名)

(Number)
(番号)

(Country)
(国名)

私は、ここに、下記のいかなる米国仮特許出願についても、その米国法典第35編第119条(e)項の利益を主張する。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、ここに、下記のいかなる米国出願についても、その米国法典第35編第120条に基づく利益を主張し、又米国を指定するいかなるPCT国際出願についても、その同第365条(c)に基づく利益を主張する。また、本出願の各特許請求の範囲の主題が、米国法典第35編第112条第1段に規定された態様で、先行する米国出願又はPCT国際出願に開示されていない場合においては、その先行出願の出願日と本国内出願日またはPCT国際出願日との間の期間中に入手された情報で、連邦規則法典第37編規則1.56に定義された特許性に関わる重要な情報について開示義務があることを承認する。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、ここに表明された私自身の知識に係わる陳述が真実であり、且つ情報と信ずることに基づく陳述が、真実であると信じられることを宣言し、さらに、故意に虚偽の陳述などを行った場合は、米国法典第18編第1001条に基づき、罰金または拘禁、若しくはその両方により処罰され、またそのような故意による虚偽の陳述は、本出願またはそれに対して発行されるいかなる特許も、その有効性に問題が生ずることを理解した上で陳述が行われたことを、ここに宣言する。

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT international application having a filing date before that of the application for which priority is claimed.

Priority Not Claimed

優先権主張なし

11 March 1999
(Day/Month/Year Filed)

☐

10 March 2000
(Day/Month/Year Filed)

☐

(Day/Month/Year Filed)

☐

(Day/Month/Year Filed)

☐

(Day/Month/Year Filed)

☐

(Day/Month/Year Filed)

☐

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)
(出願番号)

(Filing Date)
(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of application.

(Status: Patented, Pending, Abandoned)
(現況: 特許許可、係属中、放棄)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

日本語宣言書

委任状： 私は本出願を審査する手続を行い、且つ米国特許商標庁との全ての業務を遂行するために、記名された発明者として、下記の弁護士及び／または弁理士を任命する。（氏名及び整理番号を記載すること）

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

2 WILLIAM S. FROMMER, Registration No. 25,506 and
DENNIS M. SMID, Registration No. 34,930

書類送付先

Send Correspondence to:
WILLIAM S. FROMMER, Esq.
c/o FROMMER LAWRENCE & HAUG LLP
745 Fifth Avenue
New York, New York 10151

直通電話連絡先：（氏名及び電話番号）

Direct Telephone Calls to: (212) 588-0800
To the attention of: WILLIAM S. FROMMER

唯一または第一発明者氏名

Full name of sole or first inventor

1-0 Fumio NAGUMO

inventor's signature

Date

発明者の署名

日付

Residence

Kanagawa, Japan

Citizenship

Japan

Post Office Address:

Sony Corporation
7-35 Kitashinagawa 6-Chome
Shinagawa-Ku, Tokyo 141, Japan

第二共同発明者がいる場合、その氏名

full name of second joint inventor, if any

第二共同発明者の署名

日付

Second Inventor's signature

Date

住所

Residence

国籍

Citizenship

郵便の宛先

Post Office Address

（第三以下の共同発明者についても同様に記載し、署名をすること）

(Supply similar information and signature for third and subsequent joint inventors)